
# louis poulsen





## Patera

#### Design:

Øivind Slaatto

## Concept:

The pendant is a glowing sphere built up of small diamond-shaped cells. Each cell is carefully designed to capture light and to shield the light source from the viewing angles above 45 degrees. Each cell glows. Below 45 degrees, the fields are open to direct light downwards. A small amount of light is also sent upwards to illuminate the ceiling.

### Finish:

White, matt coated.

#### Material:

Shade: Cut matt PVC. Suspension: E27: Matt-chromed brass and die cast acrylic. LED: Matt white.

#### **Mounting:**

E27 ( $\emptyset$ 450/ $\emptyset$ 600): Suspension type: Cable, 2 x 1.0 mm2. E27 ( $\emptyset$ 900): Suspension type: 2x1mm² and wire. Canopy. Yes. Cord length: 4m. LED ( $\emptyset$ 450/ $\emptyset$ 600/900): Suspension type: Cable, 2 x 0.75 mm2 and wire. Canopy contains driver. Cord length: 4m.

## Weight:

Min: 0.5 kg Max: 12.1 kg

#### Class

Ingress protection IP20. Electric shock protection I w. ground (LED), II w/o ground (E27).

#### Info notes:

For LED replacement kits please do contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website www.louispoulsen.com

# PRODUCT OVERVIEW

Dimensions	CCT/Watt/ Lumen	Light source	Finish	Lighting control	Efficacy	Order-no.
Ø 450	-	1X100W E27	WHT	NONE	-	5741099003
Ø 600	-	1X200W E27	WHT	NONE	-	5741096941
Ø 600	3000K 65.0 3907	65W LED 3000K	WHT	DALI	60	5741096983
Ø 600	3000K 65.0 3907	65W LED 3000K	WHT	WIRELESS BLUETOOTH	60	5741098512
Ø 900	-	1X200W E27	WHT	NONE	-	5741098237
Ø 900	2700K	96W LED 2700K	WHT	DALI	-	5741098253
Ø 900	2700K	96W LED 2700K	WHT	WIRELESS BLUETOOTH	-	5741098541
Ø 900	3000K 96.0 5196	96W LED 3000K	WHT	DALI	54	5741098279
Ø 900	3000K 96.0 5196	96W LED 3000K	WHT	WIRELESS BLUETOOTH	54	5741098554

# **SPAREPART**

Product name: Ordering number:

CANOPY WHITE 2-PART, TOPHAT ® 5749329034